



## **TALYN**

**TALYN** is an extruded material for toe-puffs, with a "ping-pong" effect. Talyn range is available in a soft version with normal adhesive or polyurethane adhesive with two backers and a hard version with normal adhesive or polyurethane adhesive with two backers.

SOFT with TAG adhesive (non woven on one side)				
Talyn 433	0.45 0.55	Talyn 437	0.80	0.90
Talyn 435	0.65   0.75	Talyn 439	0.95	1.05
SOFT with po	lyurethane adhesiv	ve (non woven on bo	th sides)	
Talyn 473 TMS1	0.55 0.65	Talyn 477 TMS1	0.85	0.95
Talyn 475 TMS1	0.65 - 0.75	Talyn 479 TMS1	1.00	1.10
VERY SOFT w	ith TAG adhesive (	non woven on both	sides)	
Talyn 473 TAG1	0.45 0.55	Talyn 477 TAG1	0.75	0.85
Talyn 475 TAG1	0.50 - 0.60	Talyn 479 TAG1	0.95	1.05
RIGID with T	AG adhesive (non v	woven on one side)		
Talyn 402	0.35 0.45	Talyn 405	0.65	0.75
Talyn 403	0.45 0.55	Talyn 406	0.80	0.90
Talyn 404	0.55 0.65	Talyn 407	0.85	0.95
RIGID with po	olyurethane adhes	ive (non woven on b	oth sides)	
Talyn 463 APP1	0.50 0.60	Talyn 469 APP1	0.95  ▼	1.05
Talyn 465 APP1	0.65 0.75	Talyn 491 APP1	1.15 ₩	1.25
Talyn 467 APP1	0.85   0.95	Talyn 493 APP1	1.30	1.40
RIGID with T	AG adhesive (non v	voven on one side)		
Talyn 453	0.50   0.60	Talyn 455	0.65	0.75
Talyn 457	0.80 0.90	Talyn 459	0.95	1.05
EXTRA SOFT	with TAG adhesive	(raised cotton wover	on one side	)
Talyn 483	0.65 0.75	Talyn 485	0.85	0.95
<b>-</b>				

## Cutting

On the bias or flat across the widest width of the sheet (as indicated on the sheets). Way of using



The toe puff is applied by a special pneumatic pressing machine, equipped with heated curved plate, timer and thermostat.

Advisable working condition:

- temperature: 150° 170°C about.
  Contact time: from 5 to 10 seconds according to the thickness of article.

There is no binding time as to the lasting period.

## Lasting

The heat activation of the toe puff and upper is recommended.

TALYN range is made by RECYCLABLE MATERIALS and the production scraps are REGENERATED and fully RECYCLED into the production cycle.